

# 130PzS-ET 1980 SOLAR

## Vented Flooded Deep Cycle Battery



### Performance characteristics

Nominal Voltage	2V
Number of cells	1
Design Life	20 years
<b>Nominal Capacity 25°C (77°F)</b>	
120 hour rate (16.5A, 1.85V)	1981Ah
48 hour rate (38A, 1.80V)	1842Ah
10 hour rate (149A, 1.8V)	1494Ah
<b>Internal Resistance</b>	
Fully Charged Battery 25°C (77°F)	0.23mOhm
<b>Electrolyte</b>	
Nominal S.G at 25°C = 1.240kg/l	
<b>Operating Temperature Range</b>	-20-55°C
<b>Maximum Discharge Current 25°C (77°F)</b>	1585A
<b>Charge Methods: Constant Voltage Charge 25°C (77°F)</b>	
Cycle use	2.40V (time limited)
Maximum charging current	596A
Standby use	2.25V ± 1%
Temperature compensation	-3.5mV/°C/Cell
<b>Terminal Torque</b>	23Nm

### Features

- High energy density

---

- Robust tubular positive electrode design, compliant with DIN 40736

---

- Minimal maintenance due to low antimony alloy and large electrolyte volume

---

- Operating temperature -20°C to +55°C

---

- Low self discharge rate of approximately 3% per month at 20°C

---

- EUROBAT design life: Long Life >12 years

---

- Fully recyclable with low CO<sub>2</sub> footprint

---

- High cyclic performance

---

- 3000+ cycles @ 60% DOD @ IUI charging

### Capacities C10-C240

Cell Type Ue (100%) / VPC	C10	C12	C20	C24	C48	C72	C100	C120	C240
Ref Temp	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C

130PzS-ET 1980 SOLAR	1494	1561	1646	1690	1842	1970	1921	1981	2060
----------------------	------	------	------	------	------	------	------	------	------

### Applications

- Solar/Wind Power Stations

---

- Traffic Systems

---

- Hydro Power Generation

---

- Off Grid Solutions


---

- Telecommunications/ Mobile Phone Stations

---

- Power Distribution Companies

### Cycles vs DOD of OPzS Solar Power



### Dimensions and weight

Length	210 mm
Width	275 mm
Height (H1)	647 mm
Total height (H2)	660 mm
Dry weight	68.0 kg
Filled weight	91.0 kg

