

# 130PzV-ET 2113 SOLAR

## VRLA Gel Deep Cycle Battery



### Performance characteristics

Nominal Voltage	2V
Number of cells	1
Design Life	20 years
<b>Nominal Capacity 25°C (77°F)</b>	
120 hour rate (18.1A, 1.85V)	2173Ah
48 hour rate (40.7A, 1.8V)	1953Ah
10 hour rate (169.8A, 1.8V)	1698Ah
<b>Internal Resistance</b>	
Fully Charged Battery 25°C (77°F)	0.22mOhm
<b>Self-Discharge</b>	
2% of capacity declined per month at 25°C (average)	
<b>Operating Temperature Range</b>	-20-55°C
<b>Maximum Discharge Current 25°C (77°F)</b>	1681A
<b>Charge Methods: Constant Voltage Charge 25°C (77°F)</b>	
Cycle use	2.40V
Maximum charging current	823.5
Standby use	2.25V ± 1%
Temperature compensation	-3.5mV/°C/Cell
<b>Terminal Torque</b>	23Nm

### Features

- High energy density and cyclic performance

---

- Robust tubular positive electrode design, compliant with DIN 40742

---

- >1500 cycles at 80% D.O.D at 20°C (68°F)

---

- Low self discharge rate <2% @ 20°C allows for 6 months shelf life

---

- Operating temperature -20°C to +55°C

---

- EUROBAT design life: Long Life >12 years

---

- Fully recyclable with low CO<sub>2</sub> footprint

---

- 3000+ cycles @ 60% DOD @ IUI charging

### Capacities C10-C240

Cell Type Ue (100%) / VPC	C10	C24	C48	C72	C100	C120	C240
Ref Temp	25°C	25°C	25°C	25°C	25°C	25°C	25°C

130PzV-ET 2113 SOLAR	1698	1936	1953	2139	2105	2173	2241
----------------------	------	------	------	------	------	------	------

### Applications

- Solar/Wind Power Stations

---

- Traffic Systems

---

- Hydro Power Generation

---

- Off Grid Solutions


---

- Telecommunications/ Mobile Phone Stations

---

- Power Distribution Companies

### Cycles vs DOD of OPzV Solar Power



### Dimensions and weight

Length	210 mm
Width	275 mm
Height (H1)	796 mm
Total height (H2)	809 mm
Approx. weight	116.0 kg

