

# 220PzV-ET 3600 SOLAR

## VRLA Gel Deep Cycle Battery



### Performance characteristics


Nominal Voltage	2V
Number of cells	1
Design Life	20 years
<b>Nominal Capacity 25°C (77°F)</b>	
120 hour rate (30.9A, 1.85V)	3712Ah
48 hour rate (69.5A, 1.8V)	3335Ah
10 hour rate (290A, 1.8V)	2900Ah
<b>Internal Resistance</b>	
Fully Charged Battery 25°C (77°F)	0.12mOhm
<b>Self-Discharge</b>	
2% of capacity declined per month at 25°C (average)	
<b>Operating Temperature Range</b>	-20-55°C
<b>Maximum Discharge Current 25°C (77°F)</b>	2854A
<b>Charge Methods: Constant Voltage Charge 25°C (77°F)</b>	
Cycle use	2.40V
Maximum charging current	1406.5
Standby use	2.25V ± 1%
Temperature compensation	-3.5mV/°C/Cell
<b>Terminal Torque</b>	23Nm

### Capacities C10-C240

Cell Type Ue (100%) / VPC Ref Temp	C10 25°C	C24 25°C	C48 25°C	C72 25°C	C100 25°C	C120 25°C	C240 25°C
--	-------------	-------------	-------------	-------------	--------------	--------------	--------------

220PzV-ET 3600 SOLAR	2900	3306	3335	3654	3596	3712	3828
----------------------	------	------	------	------	------	------	------

### Cycles vs DOD of OPzV Solar Power



### Features

- High energy density and cyclic performance

---

- Robust tubular positive electrode design, compliant with DIN 40742

---

- >1500 cycles at 80% D.O.D at 20°C (68°F)

---

- Low self discharge rate <2% @ 20°C allows for 6 months shelf life

---

- Operating temperature -20°C to +55°C

---

- EUROBAT design life: Long Life >12 years

---

- Fully recyclable with low CO<sub>2</sub> footprint

---

- 3000+ cycles @ 60% DOD @ IUI charging

### Applications

- Solar/Wind Power Stations

---

- Traffic Systems

---

- Hydro Power Generation

---

- Off Grid Solutions

---

- Telecommunications/ Mobile Phone Stations

---

- Power Distribution Companies

### Dimensions and weight

Length	212 mm
Width	575 mm
Height (H1)	771 mm
Total height (H2)	784 mm
Approx. weight	216.14 kg

