

70PzV-ET 1050 SOLAR

VRLA Gel Deep Cycle Battery



Performance characteristics


Nominal Voltage	2V
Number of cells	1
Design Life	20 years
Nominal Capacity 25°C (77°F)	
120 hour rate (8.59A, 1.85V)	1031Ah
48 hour rate (19.3A, 1.8V)	927Ah
10 hour rate (80.6A, 1.8V)	806Ah
Internal Resistance	
Fully Charged Battery 25°C (77°F)	0.41mOhm
Self-Discharge	
2% of capacity declined per month at 25°C (average)	
Operating Temperature Range	-20-55°C
Maximum Discharge Current 25°C (77°F)	886A
Charge Methods: Constant Voltage Charge 25°C (77°F)	
Cycle use	2.40V
Maximum charging current	390A
Standby use	2.25V ± 1%
Temperature compensation	-3.5mV/°C/Cell
Terminal Torque	23Nm

Capacities C10-C240

Cell Type Ue (100%) / VPC Ref Temp	C10 25°C	C24 25°C	C48 25°C	C72 25°C	C100 25°C	C120 25°C	C240 25°C
--	-------------	-------------	-------------	-------------	--------------	--------------	--------------

70PzV-ET 1050 SOLAR	806	862	927	1015	999	1031	1064
---------------------	-----	-----	-----	------	-----	------	------

Cycles vs DOD of OPzV Solar Power



Features

- High energy density and cyclic performance

- Robust tubular positive electrode design, compliant with DIN 40742

- >1500 cycles at 80% D.O.D at 20°C (68°F)

- Low self discharge rate <2% @ 20°C allows for 6 months shelf life

- Operating temperature -20°C to +55°C

- EUROBAT design life: Long Life >12 years

- Fully recyclable with low CO₂ footprint

- 3000+ cycles @ 60% DOD @ IUI charging

Applications

- Solar/Wind Power Stations

- Traffic Systems

- Hydro Power Generation

- Off Grid Solutions

- Telecommunications/ Mobile Phone Stations

- Power Distribution Companies

Dimensions and weight

Length	145 mm
Width	206 mm
Height (H1)	643 mm
Total height (H2)	656 mm
Approx. weight	53 kg

