


QSRF 305 HC (J305)

QUASAR Flooded Carbon Nano Battery



Electrical Specifications


C5 Capacity	295Ah
C20 Capacity	350Ah
Voltage	6V
80% DOD Voltage Cutoff	5.6V
Self Discharge	Less than 3% per month (20°C/68°F)
Charge Temperature	Min: -10°C (14°F) / Max: 50°C (122°F)
Discharge Temperature**	Min: -40°C (-40°F) / Max: 50°C (122°F)
Storage	Min: -20°C (-4°F) / Max: 60°C (140°F)

Mechanical Specifications

Industry Reference	J305	
Length (A)	12.1 in	308 mm
Width (B)	6.8 in	174 mm
Height (C)	13.3 in	339 mm
Height (D)	14.4 in	365 mm
Weight	97 lbs	44 kgs
Terminal (Opt'l)	Dual	
Cell(s)	3	
Electrolyte	Flooded	
Terminal Torque Nm	STUD: 11-12Nm AP: 6-8Nm	

NOTE: There is a tolerance of +/-2%.

Capacity vs Temperature



IUI Charging

I₁ = min. 12% C₅ max. 40% C₅
 U = 2.45 V per cell
 I₂ = 6% C₅ for max. 4 hours

Features

- Ultra energy efficient due to low resistance
- Increased cycle life due to Carbon Nano Tube Technology
- Suitable for opportunity charging
- Cost savings due to increased efficiency
- Up to 2 x faster recharge
- Allows for opportunity charging to give you those extra running times when required
- Suitable for extreme temperature variants

Applications

- Golf carts, including electric vehicles
- Access Work Platform (AWP)
- Cleaning Machines
- Maritime
- Wheelchairs
- Solar & Renewable Energy
- Traffic Systems
- Caravans / Motorhomes RV's
- Home Invertor

